


认证 CE

材料 黄铜镀镍

防护等级 IP68



材料：黄铜镀镍
 夹紧件：尼龙(PA)
 密封件材料：丁腈橡胶
 温度范围：-40℃到+100℃
 短时可达+120℃
 防护等级：IP68

技术数据

型号 普通pg制螺纹	PG7	PG9	PG11	PG13.5	PG16	PG21	PG29	PG36	PG42	PG48
订货号	5014.021	5014.022	5014.023	5014.024	5014.025	5014.026	5014.027	5014.028	5014.029	5014.030
卡口范围mm	3-6	4-8	6-10	6-10	8-12	13-18	18-25	25-32	32-38	37-44
AG外径mm	12.5	15.2	18.6	20.4	22.5	28.3	37.0	47.0	54.0	59.3
GLmm	6	7	8	8	8	11	11	13	14	14
Hmm	19	20	21	22	23	25	29	35	37	38

型号 普通公制制螺纹	M12×1.5	M14×1.5	M16×1.5	M18×1.5	M20×1.5	M22×1.5	M24×1.5	M27X2
订货号	5014.046	5014.047	5014.048	5014.049	5014.050	5014.051	5014.052	5014.053
卡口范围mm	3-6	3-6	4-8	6-10	6-10	8-12	10-14	13-18
AG外径mm	12	14	16	18	20	22	24	27
GLmm	6	6	7	8	8	8	10	11
Hmm	19	19	20	21	22	22	23	25

型号 普通公制制螺纹	M30X2	M33X2	M36X2	M42X2	M48X2	M54X2	M60X2	M64X2
订货号	5014.054	5014.055	5014.056	5014.057	5014.058	5014.059	5014.060	5014.061
卡口范围mm	13-18	15-22	18-25	22-28	25-32	32-38	37-44	37-44
AG外径mm	30	33	36	42	48	54	60	64
GLmm	11	11	11	12	13	14	14	14
Hmm	25	28	29	29	35	37	38	38